



**WESTERN BLENDED
PRODUCTS**
The Plasterer's Standard

EZ-Kote Stucco

A multi-use polymer modified stucco used for leveling & skim coating cementitious and masonry surfaces, repairs and foam bonding.



Excellent for:

- Skim/Leveling
- Patching and Repair
- EPS Bonding

Use for:



Skim Coat
(Capa de nivelado)



Skim / Level Stucco
(Nivelado de estuco)



Bond/Coat EPS Shapes
(Adhesivo formas EPS)

SBS Stucco Bond & Skim



Description:

EZ-Kote Stucco is a polymer modified portland cement product designed to be used over cementitious and masonry surfaces. It may also be used to bond EPS shapes.

Features and Uses:

EZ-Kote Stucco may be used for the following applications:

- Patching hairline cracks in portland cement plaster.
- Skim coating directly over cementitious and masonry surfaces.
- A mesh embedment coat for use over portland cement.
- Bonding and plastering EPS foam shapes.

Benefits:

It is an all in one mix so every batch is accurate. It is flexible and water resistant. Provides superb adhesion to cementitious and masonry surfaces. Provides an excellent substrate for acrylic finishes to adhere to.

Packaging:

EZ-Kote Stucco is packaged in 50 lb / 22.7 kg sacks. Fifty-six sacks per pallet.

Sands Blends:

EZ-Kote Stucco is available in a super fine aggregate presentation.

Coverage:

Coverage as a skim/leveling coating at 1/16" is approximately 115 square feet per bag. Porosity of substrates will affect the coverage. Embedding mesh will require a thicker application to achieve full embedment of the mesh. It is also recommended to increase the thickness of the application over EPS foam shapes to provide more durability.

Mixing:

Each 50 Lb sack of EZ-Kote Stucco is mixed with 1.25 gallons of potable water in a clean pail and drill mixed with a paddle mixer. Initial mixing time is approximately 3 minutes or until the material is thoroughly wet. The material shall stand for 5 minutes. Add additional water as needed (up to 6 ounces.) and mix for one minute or just the time it takes to disperse the additional water.

Application as a skim coat:

Apply 1/16" thick EZ-Kote Stucco with a steel trowel over cementitious or masonry surfaces. Smooth plaster with trowel.

Application as EPS adhesive:

All surfaces to receive EPS shapes shall be moistened before application. The surface of the EPS shape shall also be scored to provide a good key for the adhesive. Apply EZ-Kote Stucco with 1/2" x 1/2" notched trowel to the back of the EPS shape. Coverage should be 100% with EZ-Kote Stucco. Press firmly into place.

Application as an embedment coat for mesh:

Embed mesh in a 1/16" thick layer of EZ-Kote Stucco. Use trowel to apply pressure to fully embed the mesh. Smooth plaster with trowel. An additional coat may be required if mesh is visible.

Application as a patching plaster:

EZ-Kote Stucco may be directly troweled over hairline cracks in cement brown coats before the application of an EZ-Kote Stucco skim coat.

For cracks larger than hairline (1/64") or 'dynamic' cracks, work EZ-Kote Stucco into the crack then apply 2" fiberglass tape over the crack. Trowel EZ-Kote Stucco over the top and another 6" to 8" in all directions from the repaired area. Feather the edges to blend into the cement substrate. Skim coat entire surface as described above.

Curing:

The product requires a minimum of forty-eight (48) hours moist curing. Environmental conditions such as heat, wind and low humidity will require additional curing.

Finishing:

A variety of finishes such as standard acrylic paints, textured acrylic finishes or elastomeric coatings may be applied over EZ-Kote Stucco. The recommendations of the finish coat manufacturer shall be followed regarding base coat preparation, acceptable pH levels, bonding, application and curing of their finish.

Limitations:

Do not add accelerator, air entrainment or other admixtures to EZ-Kote Stucco without written permission from an authorized manufacturer of Western Blended Products.

Do not apply EZ-Kote Stucco on surfaces sloped less than 30 degrees or surfaces that are below grade or subject to hydrostatic pressure.

Do not apply when surface or ambient temperatures are at or below 40°F / 4.4°C or above 100°F / 34°C. Do not apply to surfaces that are contaminated with bond breakers, oils or other matter that may affect the performance of the product. Do not apply EZ-Kote Stucco if conditions are expected to be above or below the specified temperature range within 24 hours of application. Do not add additional ingredients to EZ-Kote Stucco without specific written approval from an authorized manufacturer of Western Blended Products.

Storage:

EZ-Kote Stucco shall be kept indoors or if stored outdoors, shall be adequately covered to keep dry and be stored off the ground.

Specifications for this product are based on optimal environmental conditions (70°F ambient temperature with 50% humidity) for preparation, mixing, application and curing. Specification parameters may vary as environmental conditions change. Consult the product's Safety Data Sheet or GHS Section located on the product package for hazard identification and first aid measures. **KEEP OUT OF REACH OF CHILDREN.**

Warranty:

Manufacturers of Western Blended Products (WBP) warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WBP instructions. Manufacturers of WBP do not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at manufacturers of WBP option, to a refund of the purchase price. In the event of a claim under this warranty, written notice must be given to the originating plant of the WBP goods at the address shown hereon. This limited warranty is issued and accepted in lieu of all other expressed warranties, and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

DEC 2017

Sacramento Stucco Co.
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442
Western Stucco Co.
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455
Rio Grande Stucco Co.
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

Visit us on the web:
westernblended.com



Western Blended Products are manufactured in the U.S.A. utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

