



**WESTERN BLENDED  
PRODUCTS**  
The Plasterer's Standard


## Western 1-Kote Sanded Gray

A factory pre-mixed, fiber reinforced cementitious coating  
for One-Coat & Conventional Stucco Systems.



- *Factory sanded*
- *Fiber reinforced*
- *Cost effective*

Use for:



SB Stucco Basecoats



### Description:

Western 1-Kote Sanded Gray is designed to be a cost effective, factory sanded product for one coat wall systems. Western Western 1-Kote Sanded Gray is a cement plaster that only requires water at the jobsite. Western 1-Kote Sanded Gray may also be used over wood or gypsum backing and may be utilized for a scratch and / or brown coat application for a conventional stucco system. It is available in a "regular" as well as a "premium" blend.

The base coat is designed to be mixed with a fixed quantity of water (unlike traditional one coat products where the water varies due to the moisture content of the bulk sand.) By eliminating the variables of field mixing - every bag, every batch and every wall - are the best quality available in the industry.

### Packaging:

Western 1-Kote Sanded Gray is packaged in 80 lb / 36.29 kg bags.

### Features and Benefits:

- **Feature:** The mix is designed to be workable with a reduced amount of water.
- **Benefit:** Reduced water content increases early strength, overall strength and reduces shrinkage cracking.
- **Feature:** No field batching of sand.
- **Benefit:** Detrimental effects of poor sand and too much sand are eliminated.
- **Feature:** Western 1-Kote Premium Sanded is blended with stucco grade aggregate in lieu of low cost-dry bulk sands.
- **Benefit:** Higher strengths, and reduced shrinkage cracks.
- **Feature:** Contractors use the product with a fixed amount of water per the mixing instructions.
- **Benefit:** Every bag, every batch and every wall have the potential to develop maximum strength and durability.

### Mixing:

Western 1-Kote Sanded Gray accurately with water is critical to maximizing the benefits of the product.

Each bag shall be mixed with no more than one and one third gallons of water.

One gallon of clean potable water shall be added to the mixer before the addition of each bag of Western 1-Kote Sanded Gray. The

additional one-third gallon or 40 fluid ounces per bag may be added as the product is mixing. Mixing time in a mechanical mixer shall be two (2) to three (3) minutes per bag. Care shall be taken when continuous batching, that each bag is allowed the minimum mixing time.

### Coverage:

Approximately 2.75 sq. yds. / 2.3 square meters @ (3/8") three-eighths inch  
Approximately 2 sq. yds. / 1.7 meters square meters @ (1/2") one-half inch.

### Application:

Western 1-Kote Sanded Gray is applied by approved applicators. The material may be applied by hand or plaster pump. Specific minimum thickness is required for application over various substrates. Consult the IAPMO Evaluation Report #382 for specific details. The minimum thickness over any substrate, when used in conjunction with the Western 1-Kote System, is three-eighths (3/8") of an inch.

### Curing:

The product requires a minimum of forty-eight (48) hours moist curing. Environmental conditions such as heat, wind and low humidity will require additional curing.

### Finishing:

A variety of finishes such as Western Exterior Stucco, standard acrylic paint and Premium Acrylic Finish (PAF) may be applied over Western 1-Kote Sanded Gray. The recommendations of the finish coat manufacturer shall be followed regarding base coat preparation, bonding, application and curing of their product.

### Limitations:

Do not apply when surface or ambient temperatures are at or below 40°F / 4.4°C or above 100°F / 34°C. Do not apply to surfaces that are contaminated with bond breakers, oils or other matter that may affect the performance of the product. Do not apply Premium Sanded Western 1-Kote if conditions are expected to be above or below the specified temperature range within 24 hours of application. Do not add additional ingredients to Premium Sanded Western 1-Kote without specific written approval from an authorized manufacturer of Western Blended Products.

### Storage:

Western 1-Kote Sanded Gray shall be kept indoors or if stored outdoors, shall be adequately covered to keep dry and be stored off the ground.

### Applicable Standards, Specifications and Codes:

- IAPMO ER#382  
2018, 2015, 2012 & 2009 International Building Code (IBC).
- 2018, 2015, 2012 & 2009 International Residential Code (IRC).
- ICC-ES AC11.



### Warranty:

Manufacturers of Western Blended Products (WBP) warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WBP instructions. Manufacturers of WBP do not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at manufacturers of WBP option, to a refund of the purchase price. In the event of a claim under this warranty, written notice must be given to the originating plant of the WBP goods at the address shown hereon. This limited warranty is issued and accepted in lieu of all other expressed warranties, and expressly excludes liability for consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

DEC 2017

**Sacramento Stucco Co.**  
1550 Parkway Blvd. West Sacramento, CA 95691 / (916) 372-7442

**Western Stucco Co.**  
6101 N. 53rd. Drive Glendale, AZ 85311 / (623) 939-9455

**Rio Grande Stucco Co.**  
9151 Roseway Drive El Paso, TX 79907 / (915) 858-3494

Visit us on the web:  
**westernblended.com**



Western Blended Products are manufactured in the U.S.A. utilizing the strictest quality control processes to ensure consistent, high-performance products on every project.

